

FENCE STRENGTH FOR THE LONG RUN.



LIGHTNING[®]
FENCE DROPPERS

**Insulated
versions also
available**

FENCE STRENGTH FOR THE LONG RUN

You can slip a Lightning Fence Dropper in place in seconds with a flick of the wrist and a screwdriver. Then you can forget it for years.

Millions in use worldwide over 30 years testify to the proven durability of our 4.0mm heavily galvanised spring wire.

Lightning Fence Droppers are fireproof, weatherproof, and they stand the test of time. They're simple to remove and re-use again and again. They're economical, they suit both plain and barbed wire and they're available in 11 standard sizes to suit "Waratah" steel posts. Made-to-order measurements are also no problem.

Order from your local stock and station agent or fencing supplier.

▶ SIMPLE ECONOMICAL DESIGN

Add years to the serviceable life of your fencing and save money and stock. Lightning Fence Droppers are lightweight for maximum fence efficiency and minimum freight costs. They are easily removeable, re-usable and fire resistant, require no maintenance and suit plain or barbed wire.

▶ HEAVILY GALVANISED FOR ADDED DURABILITY

Heavily galvanised 4.0mm spring wire makes Lightning Fence Droppers flexible and resistant to time and the weather. They keep on springing back into place, and will not stay bent or break.

▶ INSULATED VERSIONS AVAILABLE TO SUIT ELECTRIC FENCING PROVEN QUALITY AND PERFORMANCE

Lightning Fence Droppers are Australian-made by an Australian-owned company, using highest quality springwire... with a track record a country mile long.


▶ COMPLETE RANGE OF SIZES

Standard sizes suit a range of 3 to 9 lines. Droppers can be supplied with overall lengths up to 120cm for any number of line wires with a minimum spacing between wires from 10cm*. Within these limitations any size required will be produced to order. When ordering please specify clearly, spacings of linewires starting from the bottom wire, or order standard sizes by colour code. Standard sizes are:

Ordering Code	Overall Length	Spacings from Bottom in cms	No. of Line Wires	Colour Code	Weight per Bundle (x25 droppers)
FD360	60cm	30-30	3	Yellow	2.41kg
FD361	61cm	28-33	3	Red	2.44kg
FD461	61cm	18-20-23	4	Green	2.67kg
FD469	69cm	23-23-23	4	Blue	2.86kg
FD476	76cm	27-26-23	4	Brown	3.04kg
FD576	76cm	15-18-20-23	5	Burgundy	3.37kg
FD478	78cm	26-26-26	4	Black	3.09kg
FD490	90cm	30-30-30	4	Lt. Brown	3.38kg
FD491	91cm	30-28-33	4	White	3.41kg
FD691	91cm	15-15-18-20-23	6	Olive	3.87kg
FD7104	104cm	13-15-15-18-20-23	7	Orange	4.8kg
FD8100	100cm	13-13-13-13-15-15-18	8	Pink	5.0kg
FD996	96cm	10-10-10-10-13-13-15-15	9	Lt. Blue	5.1kg


*measured to the nearest cm.
Droppers are sold by quantity not weight.

So Quick and Easy to Apply




STEP 1

Hold dropper against the fence, with loops parallel to the fence and engage wires with downward movement.



STEP 2

Rotate dropper anti-clockwise to lock wires in the loops.



STEP 3

Wind tails onto top and bottom wires with screwdriver or rod. To remove and reuse Lightning Fence Droppers, reverse steps 1 to 3

LIGHTNING[®]

FENCE DROPPERS

HEAD OFFICE: National Mayne Industries Pty Ltd A.B.N. 49 059 053 851
41 Holland Street, Northgate Qld 4013 PO Box 134, Nundah Qld 4012
Toll Free Phone 1800 177 615 Toll Free Fax 1800 639 029

Manufactured by Mayne Industries Pty Ltd ABN 49 059 053 851. Also manufacturers of National Nails and quality building products.
Mayne Industries accepts no responsibility for personal injury or property damage that may arise from the use of our products.